

MPix13316WIR

High Definition Torpedo IP Camera



Features

- SONY 1/3" Progressive Scan Exview HAD CCD
- 1.3 Megapixel Resolution (1280 x 960)
- 3.5~16mm Megapixel Vari-Focal Lens
- Weather Resistant Housing (IP65)
- Built in 30 IR LED
- Day & Night (Sens Up)
- Mechanically Switching IR cut filter
- Dual Codec Support (M-JPEG, MPEG-4)
- Unique digital to digital image processing technology without video quality loss
- Smart Self Installation—NVR
- Built in 3 Axis Bracket (Wall & Ceiling mount)

Specification

| | |
|------------------------------|--|
| CCD | 1/3" Progressive Scan SONY EXview HAD CCD |
| Max. Pixels | 1280 x 1024 (1.3 Mega pixel) |
| 1280 x 1024 (1.3 Mega pixel) | 1280 x 960 |
| Frame Rate | 1280 x 960 : 15fps, 640 x 480 : 30fps |
| Video Compression | Motion JPEG, MPEG-4 |
| Lens | 3.5~16mm Megapixel Vari-focal Lens |
| Weatherproof | Yes, IP65 |
| Dynamic IP Support | Yes |
| DDNS Support | Yes |
| Protocol | HTTP, FPT, TCP/IP, DHCP, ARP, DNS, ICMP, RTSP, CGI |
| Multi Connection | 10 Users |
| Bit Rate (Max) | 64Kbps ~ 8000Kbps |
| Day & Night | Sens Up x 4, 30 pcs IR LED |
| IR Cut Filter | Mechanically Switching IR cut filter |
| Zoom | 12 x Digital Zoom |
| Min. Illumination | 0 Lux (LED on) |
| Power Supply | Regulated DC12V 1A (Max) |
| Operating Temperature | 41°F ~122°F |
| Dimension | 3.11" (W) x 3.03" (L) x 6.77" (H) |
| Weight | Approximately 3.31lb |