

# SENS 212VIR



## Specifications

CCD	1/3" SONY High Sensitivity CCD II
Min.Lux	0.005 Lux( Color) 0.00004 Lux ( B/W)
Effective Pixels	768 (H) x 494 (V)
Scanning System	2:1 Interlaced
Resolution	More than 600 TV Lines (Color), More than 700 TV Lines (B/W)
Lens	2.8 ~ 12 mm Auto-Iris Lens
Backlight	BLC/HLC/OFF Selectable
Weatherproof	Yes, IP66
Video Output	1.0 Vp-p / 75
S/N (Y Signal)	52dB (AGC Off, Weight ON)
IR Range	100 ft
Sens-Up	AUTO / FIXED / OFF (Selectable Limit x2 ~ x256)
Gain Control	LOW / HIGH / OFF Selectable
White Balance	ATW / AWC / MANUAL / OUTDOOR / INDOOR
On Screen Display	Available
Motion Detection	ON / OFF ( 8 ZONE, ALARM Output )
Freeze	ON / OFF
Sharpness	ON / OFF
D N Selection	COLOR / Black & White / AUTO / EXT (Built in DC Motor Drive)
Digital Image Stabilization	ON / OFF
Privacy	ON / OFF (8 ZONES)
Flip (V-REV), Mirror (H-REV)	ON / OFF
Power Supply	DC12V / AC 24V 1000mA
Operating Temp / Humidity	14°F ~ 122°F / 30 ~ 90% RH
Dimensions	3.50" (W) x 3.5" (H) x 7.09" (D)
Weight	4.19 lb

## Features

- High Resolution (Color: 600 TV Lines, B/W: 700 TV Lines)
- 1/3" SONY High Sensitivity SUPER HAD CCD II
- New SENS DSP
- 2.8 ~ 12 mm Auto Iris Lens
- Weather & Vandal Resistant Housing (IP66)
- 24 IR LED ( 100ft IR Range )
- Day & Night (Sens Up)
- Mechanically Switching IR cut filter
- Digital Noise Reduction (DNR)
- DC12V (680mA) or AC 24V ( Dual Voltage Support )

## Dimensions (unit : inches)

