

MPix13316D

High Definition Indoor IP Dome Camera



Features

- SONY 1/3" Progressive Scan Exview HAD CCD
- 1.3 Megapixel Resolution (1280 x 960)
- 3.5~16mm Megapixel Lens
- Day & Night (Sens Up)
- Dual Codec Support (M-JPEG, MPEG-4), Dual Streaming
- Unique digital to digital image processing technology without video quality loss
- Smart Self Installation—NVR

Specification

CCD	1/3" Progressive Scan SONY EXview HAD CCD
Max. Pixels	1280 x 1024 (1.3 Mega pixel)
1280 x 1024 (1.3 Mega pixel)	1280 x 960
Frame Rate	1280 x 960 : 15fps, 640 x 480 : 30fps
Video Compression	Motion JPEG, MPEG-4
Lens	3.5~16mm Megapixel Vari-Focal Lens
Dynamic IP Support	Yes
DDNS Support	Yes
Protocol	HTTP, FPT, TCP/IP, DHCP, ARP, DNS, ICMP, RTSP, CGI
Multi Connection	10 Users
Bit Rate (Max)	64Kbps ~ 8000Kbps
Day & Night	Sens Up x 4
IR Cut Filter	Mechanically Switching IR cut filter
Zoom	12 x Digital Zoom
Min. Illumination	1 Lux
Power Supply	Regulated DC12V 500mA (Max)
Operating Temperature	41°F ~122°F
Dimension	5.04" (ø) x 3.54" (H)