

## MPix13922WIR

High Definition Outdoor Torpedo IP Camera



### Features

- SONY 1/3" Progressive Scan Exview HAD CCD
- 1.3 Megapixel Resolution (1280 x 960)
- 9~22mm Vari-Focal Lens
- Weather Resistant Housing (IP65)
- Built in 30 IR LED
- Day & Night (Sens Up)
- Mechanically Switching IR cut filter
- Dual Codec Support (M-JPEG, MPEG-4)
- Unique digital to digital image processing technology without video quality loss
- Smart Self Installation—NVR
- Built in 3 Axis Bracket (Wall & Ceiling mount)

### Specification

CCD	1/3" Progressive Scan SONY EXview HAD CCD
Max. Pixels	1280 x 1024 (1.3 Mega pixel)
1280 x 1024 (1.3 Mega pixel)	1280 x 960
Frame Rate	1280 x 960 : 15fps, 640 x 480 : 30fps
Video Compression	Motion JPEG, MPEG-4
Lens	9~22mm Vari-Focal Lens
Weatherproof	Yes, IP65
Dynamic IP Support	Yes
DDNS Support	Yes
Protocol	HTTP, FTP, TCP/IP, DHCP, ARP, DNS, ICMP, RTSP, CGI
Multi Connection	10 Users
Bit Rate (Max)	64Kbps ~ 8000Kbps
Day & Night	Sens Up x 4, 30 pcs IR LED
IR Cut Filter	Mechanically Switching IR cut filter
Zoom	12 x Digital Zoom
Min. Illumination	0 Lux (LED on)
Power Supply	Regulated DC12V 1A (Max)
Operating Temperature	41°F ~122°F
Dimension	3.11" (W) x 3.03" (L) x 6.77" (H)
Weight	Approximately 3.31lb